



4-ch Reversible Desktop High Voltage Power Supplies – see inside for 19" rack-mount

Featuring.

RH & Corrosion Kelvin Probe

New Families of Connectors from SST

OC Checklist for AT-cut PVD Quartz Crystals

Work at liquid nitrogen temperature without LN2

Gas Flow Management

newstronix



Everything Needed From Gas Source To Vacuum Chamber







Air Photoemission System (APS)

KPTechnology

The photoemission in air systems are KP Technology's newest addition to their large surface analysis range. The APS systems measure the absolute work function of a material by Photoemission in Air, with an excitation range of 3.3eV to 6.8eV. With the addition of Surface Photovoltage and Surface Photovoltage Spectroscopy modules, the full bands of semiconductors can be measured in one system; no other product can do this. Each APS system comes with the gold-standard Kelvin Probe system, capable of Contact Potential Difference Measurements, backed-up by the APS' absolute measurements.



The Relative Humidity and Corrosion (RHC) Kelvin Probe

The Relative Humidity Kelvin Probe Systems are the ideal solution for researchers investigating environmentally sensitive or corrosive materials in a controlled atmosphere. As a natural upgrade from the Kelvin Probe/Scanning Kelvin Probe packages, the Relative Humidity Chambers produces reliable, accurate and repeatable data for over a range of measurement points. The Relative Humidity is automatically controlled with a range of 10-90% (accuracy 1%), allowing for quick and easy RH control to the conditions you require.







Gamma stream

Compact, portable system for gamma ray spectroscopy. Embedded positive HV power supply, charge sensitive preamplifier and digital MCA



High Voltage HV-UHV Connectors

HV connector solutions made from alumina ceramic to metal sealing technology. Features small, compact design with weldable diameter.

Up to 50 kV / 10 amps







Micro D Connectors - 9, 15, 25 Pins!

Constructed with non-magnetic SST header and glass-ceramic sealing technology for the highest level of hermeticity. Available on weldable header or standard vacuum flanges



RX14xxET Power Supply Family

4 or 8 independent HV channels in 2U, 19" rackmount unit. Each channel features independently selectable polarity & common floating return. EPICS + LabVIEW are supported








Hermetic USB Connector for Vacuum!

Very reliable glass-ceramic sealing technology; comes in single or double ended options. The stainless steel construction allows the connector to be welded in place











X-TRONIX AG • av. de Morges 52 • 1027 Lonay • Switzerland



eNewsTronix - Products & Applications

SIGN UP NOW

Cryogenics | Gas Flow | Particle Physics | Surface Science | Thin Films | Vacuum

Our printed & electronic newsletters are important vehicles of information flow to scientists and engineers on new product innovations and their applications, discount offers, workshops and much more. So don't delay, sign up today! Go to www.xtronix.ch and click the NewsTronix navigation button. On the PDF version. click the above orange 'sign up now' button.

This mailer is sponsored by: www.SwissTronix.net



secure cyber service over 50 products & services!

DOMAIN NAMES

MARKETING TOOLS ◆

WEB HOSTING ◆ SSL & SECURITY ◆ EMAIL ACCOUNTS BUILD A WEBSITE